

E-725 Digital Piezo Controller

For 3-Axis High-Speed Precision Positioning Systems



E-725 Digital 3-channel controller with P-528 Z/tip/tilt nanopositioning system

- For Nanopositioning Systems with Capacitive Sensors
- 3-Channel Version
- Powerful Digital Controller: DSP 32-bit Floating Point, 225 MHz; 20 kHz Sampling Rate; 24-bit DAC
- Communication via Ethernet, USB, RS-232
- 4th Order Polynomial Linearization for Mechanics & Electronics
- Dynamic Digital Linearization (DDL) Option for Improved Path Accuracy
- Auto-Loading of Calibration Data from Stage ID-Chip for Interchangeability of Controller and Mechanics
- Additional High-Bandwidth Analog Control Input / Sensor Input
- Optional High-Speed Parallel I/O Interface
- Flexible Wave Generators
- Digital I/O Lines for Task Triggering
- Extensive Software Support

The E-725 digital piezo controller is a compact, high-performance drive electronics for nanopositioning systems with up to three axes. High-power amplifiers permit dynamic scans even for piezo systems with large range or direct drive. State-of-the-art processor technology optimizes the operating parameters for improved linearity and tracking accuracy. High-resolution D/A converters provide for nanopositioning that deserves this name.

With the E-725.3CM, PI for the first time offers a digital controller for the P-363 PicoCube™ (see p. 2-66), a fast precision scanner for atomic force microscopy.

Optional interfaces and analog in- and outputs make it possible to process external sensor or control values.

Digital Linearization and Control Algorithms for Highest Accuracy

Linearization algorithms based on higher-order polynomials improve the positioning accuracy to better than 0.01% for capacitive sensors, typically 10 times better than achievable with conventional controllers.

More than just a Controller – Trajectory Control and Data Recording

During fast periodic motion, as typical for scanning applications, the tracking accuracy can

Ordering Information

E-725.3CD

Digital Multi-Channel Piezo Controller, 3-Channel, Sub-D Connector for Capacitive Sensors

E-725.3CM

Digital Multi-Channel Piezo Controller, for PicoCube™ and Capacitive Sensors

Ask about custom designs

be further improved with Dynamic Digital Linearization (DDL, E-710.SCN). This optionally available control algorithm reduces the tracking error by a factor of up to 1000.

This control algorithm enables the spatial and temporal tracking during a dynamic scan. The integrated wave generator can output periodic motion profiles. In addition to sine and triangle waves, arbitrary, user-defined motion profiles can be created and stored. The flexibly configurable data recorder enables simultaneous recording and read-out of the corresponding data.

Extensive Software Support

The controllers are delivered with Windows operating software. Comprehensive DLLs and LabVIEW drivers are available for automated control.

Automatic Configuration

PI digital piezo controllers and nanopositioning stages with ID-Chip can be operated in any combination, supported by the AutoCalibration function of the controller. Individual stage data and optimized servo-control parameters are stored in the ID-Chip and are read out automatically by the digital controllers.

Technical Data

Model	E-725.3CD	E-725.3CM	Tolerance
Function	Digital Controller for Multi-Axis Piezo Nanopositioning Systems with Capacitive Sensors	Digital Controller for Multi-Axis Piezo Nanopositioning Systems with Capacitive Sensors	
Axes	3	3	
Processor	DSP 32-bit floating point, 225 MHz	DSP 32-bit floating point, 225 MHz	
Sampling rate, servo-control	20 kHz	20 kHz	
Sampling rate, sensor	20 kHz	20 kHz	
Sensor			
Servo characteristics	P-I, two notch filters	P-I, two notch filters	
Sensor type	Capacitive	Capacitive	
Sensor channels	3	3	
Sensor bandwidth (-3 dB)	5.6 kHz	5.6 kHz	max.
Sensor resolution	18 bit	18 bit	
Ext. synchronization	Yes	Yes	
Amplifier			
Output voltage	-30 to 135 V	-250 to 250 V	±3 V
Amplifier channels	4	4	
Peak output power per channel	25 W	47 W	max.
Average output power per channel*	10 W	10 W	max.
Peak output current per channel	190 mA	190 mA	max.
Average output current per channel*	120 mA	60 mA	max.
Current limitation	Short-circuit proof	Short-circuit proof	
Resolution DAC	24 bit	24 bit	
Interfaces and operation			
Communication interfaces	Ethernet, USB, RS-232	Ethernet, USB, RS-232	
Piezo / sensor connector	Sub-D special connector	Sub-D special connector	
Analog input	1 x Lemo, ±10 V, 18 bit	1 x Lemo, ±10 V, 18 bit	
Digital input / output	MDR20; 2 x IN, 8 x OUT	MDR20; 2 x IN, 8 x OUT	
Command set	PI General Command Set (GCS)	PI General Command Set (GCS)	
User software	NanoCapture™, PIMikroMove™	NanoCapture™, PIMikroMove™	
Software drivers	LabVIEW driver, DLLs	LabVIEW driver, DLLs	
Supported functionality	Wave-Gen, Trigger I/O	Wave-Gen, Trigger I/O	
Display	LEDs for Power, On Target, Error, Cmd	LEDs for Power, On Target, Error, Cmd	
Linearization	4th order polynomial, DDL (Dynamic Digital Linearization)	4th order polynomial, DDL (Dynamic Digital Linearization)	
Separate protective ground connector	Yes	Yes	
Miscellaneous			
Operating temperature range	5 to 50 °C	5 to 50 °C	
Overheat protection	Max. 71 °C, deactivation of the piezo voltage output	Max. 71 °C, deactivation of the piezo voltage output	
Mass	3.5 kg	3.6 kg	
Dimensions	263 x 89 x 302 mm (with handles)	263 x 89 x 302 mm (with handles)	
Power consumption	70 W	70 W	max.
Operating voltage	24 VDC from external power supply (included)	24 VDC from external power supply (included)	

* The total output power of all 4 amplifier channels should not exceed 34.5 W to avoid overcurrent (E-725 is equipped with a 3.15 AM fuse).

Linear Actuators & Motors

Nanopositioning / Piezoelectrics

Piezo Flexure Stages / High-Speed Scanning Systems

Linear

Vertical & Tip/Tilt

2- and 3-Axis

6-Axis

Fast Steering Mirrors / Active Optics

Piezo Drivers / Servo Controllers

Single-Channel

Multi-Channel

Modular

Accessories

Piezoelectrics in Positioning

Nanometrology

Micropositioning

Index